

DIX TIG GO 1406.M HF PRO

SINGLE PHASE
SUITABLE FOR 230 V

7,5 KG
TOTAL WEIGHT

THE LITTLE TIG EXPERT

Latest inverter technology

High frequency ignition
or by „Lift“-Arc

PULSE TIG WELDING
from 0,5 up to 2.000 Hz

SWITCH function for continuous
change between two
preselected values



WELDING CURRENT RANGE
5 - 200 A

CONNECTION VOLTAGE
230 V +/- 20%

WEIGHT
7,5 kg



120 A, 100%

200 A, 25%

SYNERGIC SELECTION OF PULSE PARAMETER VALUES

DETAILS THAT MAKE THE DIFFERENCE

The design of the DIX.M manual power sources has been meticulously thought-out in order to fit perfectly into everyday processes and to provide the welder with the best possible support in his work.

These include, among other things, the robust and high-quality workmanship of the metal housing, which has no interfering contours, the stable and tinted display cover hoods or the easy accessibility of all control elements.

All DINSE power sources are equipped with the original DINSE sockets to guarantee a perfect power transfer.

EASY TO USE

The clearly structured control panels of the DINSE manual power sources DIX.M enable intuitive operation of the devices. All relevant welding parameters are set in an instant.

Thanks to the innovative welding software, even a less experienced welder can quickly and easily produce high-quality welds.

ACCESSORIES



- ① RC 1 foot remote control
- ② RC 2 manual remote control

QUALITY AND PERFORMANCE - WITHOUT COMPROMISE

Our DINSE manual welding torches for MIG/MAG and TIG complete your power source to a top class welding system. All information as well as suitable spare and wear parts can be found in our product catalogue.

Your DINSE expert will be pleased to advise you on the required additional equipment for your individual application.

TECHNICAL DATA

		TIG	MMA
Connection voltage <small>1-ph 50/60 Hz</small>	V <small>+/-20%</small>	230	230
Input power @ I_2 MAX	kVA	8,5	9
Delayed fuse (I_{eff})	A	20	20
Power factor / $\cos \varphi$		0,67/0,99	0,67/0,99
Efficiency degree		0,82	0,84
Open circuit voltage	V	88	88
Current range	A	5 - 200	5 - 160
Duty Cycle (40°C)	A <small>100%</small>	120	110
	A <small>60%</small>	140	130
	A <small>(X%)</small>	200 (25%)	160 (30%)
Weight		7,5 kg	
Standards		EN 60974-1 · EN 60974-3 · EN 60974-10 S	
Protection class	IP	23 S	
Insulation class		H	
Dimensions		390 mm x 135 mm x 300 mm	



DINSE is your dependable partner for the entire welding process. Contact us and schedule an appointment for consultation today. Together with you we will find the best solution for your application.

+49-(0)40-65875-0

info@dinse.eu

DINSE G.m.b.H. · Niewisch 9 · 22848 Norderstedt · www.dinse.eu

Your DINSE Partner: